



HERMES

LACQUER SANDING BEFORE POLISHING

Long belt applications



for an
excellent finish

HERMES LONG BELTS BRILLIANT RESULTS

as a perfect preparation
of lacquered surfaces
before polishing



OUR PRODUCT RECOMMENDATIONS

ALUMINUM OXIDE



BRILLIANCE FILM FC 164-LONGLIFE VEL

Extremely stable and flexible long-term aluminum oxide film abrasive belt with new film backing

Backing stability

SURFACE QUALITY

Service life

Coating

Semi-open

Backing

Film,
velour-backed

- New film backing with high edge stability and tear resistance as well as high flexibility and low weight
- Excellent surface quality and service life at constant removal rates
- Very good adaptability to contours
- Semi-open coating and optimized long-life coating prevent premature clogging
- Good strip running properties
- Fast product identification due to grain size readable on the grain side

Bonding

Resin,
active ingredient coated

Grit range

P 240, P 320,
P 400 - P 2000



FB 637

Extremely stable long time film abrasive belt with aluminum oxide grain

BACKING STABILITY

SURFACE QUALITY

Service life

Coating

Closed

Backing

Film

- High tear and compression resistant film backing leads to consistent application parameters and narrow tolerance ranges of roughness characteristics
- Uniform grain orientation ensures excellent surface qualities
- Very good strip running properties
- High material removal due to sharp abrasive grain with high bonding strength
- Good tool life, shortened processing times

Bonding

Resin

Grit range

P 120, P 180, P 240, P 280,
P 360 - P 1500, P 2500, P 4000

SILICON CARBIDE



BS 119-LONGLIFE

Stable silicon carbide abrasive belt on paper backing

BACKING STABILITY

Surface quality

Service life

Coating

Closed

Backing

D-weight paper

- Good service life for intermediate sanding of UV-cured coating systems
- Dust-free operation due to long-life stearate coating and antistatic product structure
- Stable but at the same time flexible D-paper for „soft“ lacquer sanding
- Particularly suitable for sanding clear coats

Bonding

Resin, antistatic and active
ingredient coated

Grit range

P 240 - P 600

Do you still have questions? Please contact us.

You will find your contact person on our website hermes-abrasives.com in the „Contacts“ section.

HERMES SCHLEIFMITTEL GMBH
Luruper Hauptstrasse 106 • 22547 Hamburg • Germany
www.hermes-abrasives.com

 **abrasives
safety**
www.abrasivessafety.com

